INTERIOR FILM

METAL SERIES

























SYMPHONY SERIES

SKIN-TOUCH SERIES

PLAIN SERIES







































































MARBLE SERIES

LEATHER SERIES

CEMENT GREY SERIES

FABRIC SERIES

WOOD GRAIN SERIES


IMG_0001

IMG_0002

IMG_0003

IMG_0004

IMG_0005

IMG_0006

IMG_0007

IMG_0008

IMG_0009

IMG_0010

IMG_0011

IMG_0012

IMG_0013

IMG_0014

IMG_0015

IMG_0016

IMG_0017

IMG_0018

IMG_0019

IMG_0020

IMG_0021

IMG_0022

IMG_0023

IMG_0024

IMG_0025

IMG_0026

IMG_0027

IMG_0028

IMG_0029

IMG_0030

IMG_0031

IMG_0032

IMG_0033

IMG_0034

IMG_0035

IMG_0036

IMG_0037

IMG_0038

IMG_0039

IMG_0040

IMG_0041

IMG_0042

IMG_0043

IMG_0044

IMG_0045

IMG_0046

IMG_0047

IMG_0048

IMG_0049

IMG_0050

IMG_0051

IMG_0052

IMG_0053

IMG_0054

IMG_0055

IMG_0056

IMG_0057

IMG_0058


IMG_0059

IMG_0060

IMG_0061

IMG_0062

IMG_0063

IMG_0064

IMG_0065

IMG_0066

IMG_0067

IMG_0068

IMG_0069

IMG_0070

IMG_0071

IMG_0072

IMG_0073

IMG_0074

IMG_0075


CA129


CA128


CA127


CA126


CA125


CA124


CA123


CA122


CA121


CA120


CA119


CA118



CA117



CA116


CA115


CA114


CA113


CA112



CA111


CA110


CA109


CA108


CA107



CA106


CA105


CA104


CA103


CA102


CA101

The INTERIOR FILM decorative film is an innovative material that integrates eco-friendly, flame resistance, waterproofing, moisture resistance, scratch resistance, stain resistance, antibacterial, mold resistance and formaldehyde-free properties. The main component of the product is PVC, serving as a substitute for materials such as wood veneer panels, paint-free boards, and solid wood boards. It can efficiently and rapidly refinish and renovate various material surfaces, offering advantages such as convenience, speed, and cost-effectiveness. It is suitable for interior decoration and design in various occasions. INTERIOR FILM is one of influential brands in this innovative decorative material field. The flame resistance of INTERIOR FILM decorative film meets B1 and A2 levels of GB testing standards, complying with EU environmental standards. The selection of high-quality base film and German glue, which has better performance and stronger adhesion, combining strict and high-tech production processes, provides our products with numerous significant advantages: strong weather resistance, fade resistance, a soft touch, tear-resistant, strong tensile, high temperatures resistance and clear embossing.

PRODUCT PARAMETER:

Thickness: 180UM
Air channel release paper: 140G
Glue Tensile Strength: 2500g-3000G
Cold resistance: (10-20)
Flame retardant grade: B1/A2
Specifications: 1.22M*50M(accept customization)